

REMARKS


This Preliminary Amendment is being submitted in order to further prosecution of this application.

The specification is being amended to improve its form. No "new matter" is being added. In addition, original claims 1-3 are being replaced by new claims 4-7, the form of which is consistent with the claim drafting requirements of the Patent and Trademark Office.

It is submitted that this application is now in condition for examination on the merits. If any questions arise, the Examiner is invited to telephone the undersigned attorney at the below-listed telephone number.

No fee is incurred by the Preliminary Amendment.

Respectfully submitted,
György SZEKERES et al

By: 

Joseph G. Seeber
Reg. No. 27,719

Post Office Box 750
Great Falls, VA 22066
Telephone: (703)430-1702
Facsimile: (703)450-7914

MARKED UP COPY OF AMENDED SPECIFICATION

~~Tissue micro array building manual set~~
Tissue Micro-Array Building Manual SetTechnical Field

[001] The ~~object of our~~ invention [[is]] generally relates to a tissue micro-array (TMA) preparing-building manual apparatus-set, which includes a tissue core punch extractor and a TMA block mould with lower and upper parts.

[002] The tissue micro-array preparing-building manual apparatus- set is suitable for making TMA series, which enables the fast and accurate "home-made" preparation of TMA series well-fitted to the traditional, routine histology laboratory conditions.

Background Art

[003] TMA technology can be applied for the determination of diagnostic markers, as well as[[,]] parameters [[on]] related to the aggressiveness and other features of malignant tumors.

[004] TMA is very useful for retrospective studies, i.e., for the investigation of thousands of molecular biological markers in thousands of histological specimens stored in pathology laboratories.

[005] Similar to the DNA-chip, which allows the analysis of the genome mutations and abnormal gene expressions, the tissue micro-arrays enable the parallel processing of biological specimens. By using only one TMA, researchers have [[he]] the opportunity for simultaneous comparative examination of various molecular parameters (DNA, RNA molecular biological techniques and immunohistochemistry/immunocytochemistry of antigens) in histological specimens of several malignant tumor tissues.

[006] Numerous monoclonal antibodies, which determine the genome and phenotype of intact and pathological (mainly malignant) cells, and which are specific for novel antigen-determinants, are being developed and introduced for diagnostic and therapeutic applications (immunomorphology). Diagnostic measures based on genetic methods, which can identify certain segments of DNA and/or RNA, are increasingly used (molecular biology). Several laboratories are involved in evaluating their tissue reactivity and potential applicability in the most prevalent tumors.

[007] As a consequence, this diagnostic technique indeed seems to be widely used.

[008] In the diagnostic technique, histology specimens from different tumor tissues [[re]]are embedded in properly arranged sets into paraffin for the preparation of TMA. The TMA block is cut giving the various tumor tissues as point-like items in the histological light microscopic sections. Since each TMA block may render hundreds of parallel, 3-4 [[?m]]micrometers thick serial sections, hundreds of molecular parameters can be examined on the same micro-array. Several tumor markers can be analyzed within weeks, while this would take months per tissue specimen using the traditional method.

[009] According to our current knowledge, reactions made on standard-size histological sections (from frozen and/or fixed-embedded tissues) and cytological samples (smears, sediments, imprints, cytocentrifugates, etc.) are useful for the identification [[o]]of molecular markers of tumors and for the prediction of disease progression. At the same time, merely only a limited number of samples can be examined due to technical and financial reasons, the evaluation is time-consuming[[,]] and comparative, as well as, and reproducible examinations among different laboratories are difficult to carry out. First of all, the lack of reproducibility is the disadvantage of the so-called "multi-tissue 'block'" technique that contains parts from various tissues/blocks in a simple histological block. Moreover, the distribution of individual molecular markers within the malignant tissue is often quite heterogeneous and, thus, a minute tissue part does not properly represent the biological features of the entire tumor cell population.

[010] Application of the technique reminiscent of or rather based on the "chip" technology, i.e. the tissue micro-arrays, enables the investigation of hundreds or thousands of tissue specimens.

[011] The knowledge in the field of medical biotechnological basic research is being multiplied, and its employment confirms both diagnostic and therapeutic measures. Nevertheless, the related applied research, research and development (R&D), as well as, and clinical testing processes require years or even a decade and proportional financial means. [[Our]] In accordance with our invention, the TMA building manual set shortens the necessary testing phase in an accurate and cost-efficient way.

[012] The information in the No. 4,820,504 US patent U.S. Patent No. 4,820,504 represents a well-known and widely used procedure, which serves for the preparation of a sample containing multiple tissue specimens. Its advantages include the simple procedure that can be applied in almost

every laboratory equipped with routine and research facilities, low costs, and no need for procurement of new devices. However, the disadvantage of the technique is that the consecutive, side by side embedded tissue samples are randomly situated, not organized into lines and columns, which makes the evaluation rather difficult, and the automatic (image analyzing) processing almost impossible or complicated and slow[;]]. In addition, the size of the individual tissue samples are merely roughly similar to each other. [[New]] A new instrument does not belong to is not set forth in the description of the procedure.

[013] Our procedure and the object of our invention [[aims]] are aimed at addressing these disadvantages.

[014] ~~The No. 5.002.377 US patent is a U.S. Patent No. 5.002.377 discloses an~~ instrument[[,]] which organizes tissue samples into regular lines and columns, and so gives a multiple tissue block. Its patent holder is the same as that of the previous instrument who is a well-known expert [[on]]~~in~~ this field, despite although this technique has not become widely used. Its obvious advantage is that application of this instrument enables the preparation and embedding of regular, almost identical size tissue samples. Nevertheless, its disadvantage lies in the fact that the individual tissue columns may be, though only slightly, shifted during block preparation. The largest disadvantages of the instrument are[[:]] its incompatibility with the most frequently applied and best known laboratory instruments (devices and semi-fixed assets) and, on the other hand, the need for three additional tools and the significant manual skills for their application. The first instrument includes multiple parallel cutting plates, which can cut out tissue columns from tissue samples, but which can be applied exclusively on larger specimens. The other two components make possible the embedding of cut tissue columns into a single paraffin block.

[015] ~~The No. 6.103.518 US patent is U.S. Patent No. 6.103.518 discloses~~ a table device giving useful tissue micro-arrays. The procedure is based on the well-oriented technique of the recipient places of the paraffin block and the sampling from the selected sites of donor blocks (tissue cores). Besides its aforementioned advantages, its high price, complicated mechanical settings, and the need for one-by-one preparation of recipient holes of the recipient block represent serious drawbacks in the daily practice.

[016] PCT Publication document number No. WO 01/51910 presents a simple paraffin block construction procedure that can be used for the production of tissue micro-array series in which a mould that consists of several elements has been formed. On using the mould, a basic body is moulded that has regularly arranged openings into which the tissue samples are then placed. Following this, the basic body containing the tissue samples is heated up to the softening temperature limit in the interest of the basic body being able to combine with the liquid paraffin poured onto one of the surfaces in the following phase of the procedure and so form a single unit with it. This liquid paraffin layer serves to assist in the fixing of the paraffin block holder to the paraffin block containing the cylindrical holes and the tissue samples contained in them.

[017] However, a significant disadvantage of this solution is that the paraffin block that contains the cylinders with the tissue samples in them is subjected to a significant heat effect. Due to the heat effect and the re-softening of the paraffin, the tissue cylinders move, which can cause problems when making the sections. Another disadvantage of the subsequent heat effect is that the amount of heat required to soften the paraffin may damage the tissue sample cylinders, which may cause irreversible damage from the point of view of the immune staining, as this results in a change to the protein-based antigens, and this can lead to the sample being unusable.

[018] Another significant disadvantage of the solution is that, in the paraffin block poured in two phases, due to the shear forces occurring when producing the section, the paraffin block may come apart at the border between the two layers made at two separate points in time, as a result of which the paraffin block may separate from the block holder, [[so]] making it impossible to make the desired sections from the tissue cylinders.

[019] Examples suitable for the production of paraffin blocks used for the production of tissue samples can also be found in ~~patent specification registration number US 6.383.801 U.S. Patent No. 6.383.801~~ and, furthermore, in ~~publication documents numbers PCT Publication Nos.~~ WO 01/98525, WO 99/44063, WO 01/22086 and WO 01/42796.

Disclosure of Invention

[020] The objective of our invention is to eliminate the disadvantages of the above mentioned methods and to design a tissue micro-array ~~preparing building~~ manual apparatus set that is simple,

cheap, and compatible with all widely used histological laboratory fixed and semi-fixed assets. The principle of applying the manual apparatus is that the preparation of the recipient block is separated from the sampling; ~~therefore~~. Therefore, the samples can be previously prepared and stored elsewhere, then put into the recipient block. The manual apparatus requires small space[[,]] and is easy to clean, there is basically no need for maintenance, each part is resistant to external physical and chemical impacts, and the recipient block can be prepared in one step.

[021] Our invention is based on the recognition that the tissue micro-array preparing-building manual apparatus-set should be made from elements ~~that~~ which fit together in their size, and which can be applied along with the instruments used under the traditional routine histological laboratory conditions. This tissue micro-array preparing manual apparatus set was developed to contain a tissue core punch extractor and a TMA block mould with lower and upper parts, and the traditional, most frequently used paraffin block holders fit well [[to]] with this latter one. The tissue core punch extractor is a well-known technical solution, i.e., its function is based on punching. The punching tip is made as a punching tube with an internal diameter of 1 or 2 mm. This punching tube receives the tissue cylinder (core) taken from a given place of the sample (donor block), which can be manually pushed out from the punching tip by help of a piston-like needle probe pushed back by a coil spring inside the instrument. The external diameter of the needle probe is comparable to the internal diameter of the punching tip, but due to its size it can freely slide within the punching tip.

[022] The TMA block mould is made up of two main elements: the lower and upper parts: The lower part is equipped with 1 or 2 mm wide mandrels, identical with the diameter of the punching tube, organized into lines and columns. Since the lower and upper parts are assembled together during the casting of the paraffin block and the paraffin is poured into the hole formed by the upper part, a margin should have been prepared there, which margin is identical in its size and shape [[with]] to the size and shape of the generally used paraffin block holder.

[023] The formation of the margin creates the opportunity to fix the paraffin block holder itself to the empty paraffin block in one step when moulding the paraffin block. This, later on, makes it unnecessary to carry out the subsequent heat treatment, which is essential in the known procedures, and [[so]] thus overcomes the disadvantageous consequences presented above and deriving from [[the]] heat treatment.

[024] At the lower part, at least two vertical directing ~~nipples~~ are built into the base unit, which ensures the parallel and intact removal of the paraffin block when the mould manual apparatus is taken apart. The equal withdrawal of the two elements at the opening of the lower and upper part of the TMA block mould is ensured by at least two diagonally arranged threaded arms.

[025] The elimination of the above discussed disadvantages is ensured by a tissue micro-array preparing ~~building~~ manual apparatus set with the following characteristics: a ~~by itself already known~~ tissue core punch extractor and a TMA block mould, ~~which the latter~~ ~~[[has]]~~ ~~having~~ a lower and upper part; the lower part is organized in the middle into lines and columns, set up with mandrels at right angles to the base unit; the upper part is prepared with a margin-containing cleavage, which receives the mandrels when the TMA block mould is assembled together; the margin and size of the cleavage fit ~~[[to]]~~ the shape and size of the paraffin block holder; the lower and upper parts are connected to each other with directing nipples and threaded arms fixed horizontally; the lower part of the TMA block mould has at least two vertical directing nipples, which vertically and detachably join into the bore-holes of the upper part; and, in the upper part of the TMA block mould, there are at least two diagonal transit bore-holes, which receive the threaded arms, and the endings of the threaded arms sit on the lower part when the TMA block mould is assembled together.

Brief Description of Drawings

[026] Our invention, the TMA building manual set, is presented in detail by means of the following drawings.

[027] Figure 1[[.]] depicts an Axonometric axonometric delineation of the TMA block mould.

[028] Figure 2[[.]] depicts an Axonometric axonometric delineation of the TMA block mould and paraffin block holder of the TMA building manual set.

[029] Figure 3[[.]] depicts a [[The]] finished paraffin block with the tissue core punch extractor.

Detailed Description

[030] The [[1]] TMA block mould_1 shown [[on]] in Figure 1[[.]] is made up of two major elements, i.e., [[2]] lower part_2 and [[3]] upper part_3. The [[2]] lower part_2 has [[4]] mandrels_4 with 1 or 2 mm diameter arranged into lines and columns. The diameter of the [[4]] mandrel_4 is identical [[with]] to the diameter of the [[8]] punching tube_8 of the [[14]] tissue core punch extractor_14. On the [[2]] lower part_2, there are [[5]] directing nipples_5 at right angles to the lower part_2, which ensure the parallel and intact removal of the paraffin block when the [[1]] TMA block mould_1 is dismantled. The size of the [[3]] upper part_3 is identical [[with]] to that of the [[2]] lower part_2 and, in the middle, it has a ~~margin-containing~~ cleavage_6 containing a margin_7, which receives the [[4]] mandrels_4. The [[7]] margin_7 of the [[6]] cleavage_6 is made to receive the commercially available [[12]] paraffin block holder_12 shown [[on]] in Figure 2. On the [[2]] lower part_2, there are [[5]] directing nipples[[.]]_5 which join the [[10]] transit bore-holes_10 on the [[3]] upper part_3. Moreover, the additional [[11]] transit bore-holes_11 on the [[3]] upper part_3 receives receive the [[9]] threaded arms_9, which ensure the even and parallel opening of the two parts of the assembled instrument cast with paraffin block.

[031] The equal withdrawal of the two elements at the opening of the [[2]] lower part_2 and [[3]] upper part_3 of the [[1]] TMA block mould_1 is ensured by at least two diagonally arranged [[9]] threaded arms_9. The [[14]] tissue core punch extractor_14 ends in a [[8]] punching tube_8 with an internal diameter of 1 or 2 mm.

[032] The well-known [[14]] tissue core punch extractor_14 receives the tissue cylinder taken from a given place of the sample (donor block), which can be manually pushed out from the [[8]] punching tube_8 by [[help]] means of a piston-like needle probe (not shown) pushed back by a coil spring (not shown) inside the instrument.

[033] The external diameter of the needle probe is comparable to the internal diameter of the [[8]] punching tube_8, but due to its size, it can freely slide within the [[8]] punching [[tip]] tube_8.

[034] On preparing the paraffin block, the assembled [[1]] TMA block mould_1 is filled with paraffin through the [[6]] cleavage_6. After the paraffin is set when cooled down and removed from the instrument, it gives a [[13]] paraffin block (recipient block)_13 containing 1 or 2 mm wide cylindrical holes with parallel longitudinal axes organized into regular lines and columns. These holes

receive the tissue cores having the same diameter taken out [[from]] of the donor blocks by the [[14]] tissue core punch extractor 14, giving finally the TMA block.

[035] As [[it]] can be seen from [[our]] the above description, our objective was accomplished by the development of our invention. The TMA building manual set is a simple, cheap manual instrument, which is easy to handle and clean, environment-friendly, and enables the fast and accurate preparation of TMA under the traditional, routine histological laboratory conditions.

[036] A further advantage is that, due to the unique formation of the manual set, it is possible to produce the paraffin block with a holder in one step without any subsequent heat treatment, which [[does]] not only ~~reduced~~reduces the time required for [[the]] production, but also has a favourable effect on the mechanical characteristics of the finished piece, that is, also including [[the]] shearing strength.